

Cubo Low-Voltage Track



Electrical system


Total power consumption:	9W
Power input:	48V
Operating temperature:	-10°C ~ 35°C
Dimming option:	0-10V / Dali / Casambi
Insulation class:	Class III

Light source

LED type:	SMD
CCT:	2700K/3000K/4000K/Tunable
CRI:	Ra>90
Beam angle:	7°/15°/24°/38°/10°x35°/Honeycomb
UGR:	<16

- White
- Black

Features




Housing

Lamp body diameter:	56.3mm x 56.3mm
Material:	Aluminum
Weight:	304.6g

Warranty

Period:	5-year warranty
----------------	-----------------

Dimensions




Lumen output * The lumen output is measured by the original optics (7°).

BA. \ CCT	2700K	3000K	4000K
7°	405lm	450lm	500lm

Nomenclature

*Applicable model: M40510xx90xxxx (xx: dynamic codes)

Product Code	System Power	CCT	CRI	Beam Angle	Driver/Control	Serial No.		
M405	09(9W)	27(2700K)	90(90)	07(7°)	N(Non-Dim)	01(Black)		
		30(3000K)		15°(15°)		A(0-10V dim)	02(White)	
		40(4000K)		24°(24°)	D(Dali DT6)			
				38°(38°)				
				X1(10°x35°)				
					HC(Honeycomb)			
					TW(Tunable)			
					18(18°)	E(Dali DT8)		
					24(24°)			
					38(38°)			



Illuminance distance data

Cubo

9W



7°

h(m)	E(lx)	Ø (m)	S_B(sq.m)
1	6525.81	0.18	0.025
2	1631.45	0.37	0.1
3	725.09	0.55	0.3
4	407.86	0.74	0.4
5	261.03	0.92	0.7