


FlexRay S70-1





3-phase track light.
Integrated power supply.

- White
- Black

Features



Dimensions



Tolerance: ±2mm

Electrical system

Total power consumption:	4 W
Power input:	100-265Vac, 50/60Hz
Operating temperature:	-10 °C ~ 35 °C
Power factor:	>0.95
Protection class:	Class II
Control protocol:	Non-DIM / 0-10V / DALI / Bluetooth

Light source

LED type:	SMD
Luminous flux:	220 lm
Colour temperature (CCT):	2700 K / 3000 K / 4000 K
Colour consistency (SDCM):	≤2
Colour rendering index (CRI):	Ra ≥90
Beam angle (BA):	5°

Housing

Material:	Aluminium
Weight:	x,x kg

Warranty

Period:	5 years
---------	---------

Nomenclature

Type	Series name	System power	CCT	CRI	Beam angle	Control	Colour
TL02	FlexRay	04 (04W)	40 (4000K)	90 (90)	05 (5°)	N (Non-Dim)	01 (Black)
			30 (3000K)			A (0-10V Dim)	02 (White)
			27 (2700K)			D (DALI)	
						5 (Bluetooth)	

*Applicable model: TL0204xx9005xxx (xx: dynamic codes)

Accessory

Filter	Order no.
HoneyComb	



FlexRay *S70-1*

Luminous intensity distribution curves

BA 5°

H (m)	E _n (lx)	S (sq.m)
1	11048	0,006
2	2762	0,027
3	1227	0,062
4	690	0,108
5	414	0,172

