


FlexRay S71-2





3-phase track light.
Integrated power supply.

- White
- Black

Features



Dimensions



Tolerance: ±2mm

Electrical system

Total power consumption:	27 W
Power input:	100-265Vac, 50/60Hz
Operating temperature:	-10 °C ~ 35 °C
Power factor:	>0.95
Protection class:	Class II
Control protocol:	Non-DIM / 0-10V / DALI / Bluetooth

Light source

LED type:	SMD
Luminous flux:	2300 lm
Colour temperature (CCT):	2700 K / 3000 K / 4000 K
Colour consistency (SDCM):	≤2
Colour rendering index (CRI):	Ra >90
Beam angle (BA):	9°
- Filter (optional):	15° / 20° / 30° / 40° / 50° / 70° / 20x60° / Wallwash - HoneyComb

Housing

Material:	Aluminum, plastic
Weight:	x,x kg

Warranty

Period:	5 years
---------	---------

Nomenclature

Type	Series name	System power	CCT	CRI	Beam angle	Control	Colour
TL02	FlexRay	27 (27W)	40 (4000K)	90 (90)	09 (9°)	N (Non-Dim)	01 (Black)
			30 (3000K)			A (0-10V Dim)	02 (White)
			27 (2700K)			D (DALI)	
						5 (Bluetooth)	

*Applicable model: TL0227xx9009xxx (xx: dynamic codes)

Accessory


Filter - Beam angle (BA)	Order no.	Filter	Order no.
15°		 HoneyComb	
20°			
30°			
40°			
50°			
70°			
20x60°			
Wallwash			

FlexRay *S71-2*

Luminous intensity distribution curves


BA 9°

H (m)	En (lx)	S (sq.m)
1	28501	0.03
2	7125	0.1
3	3166	0.2
4	1781	0.4
5	1140	0.6



BA 15°

H (m)	En (lx)	S (sq.m)
1	11514	0.1
2	2878	0.2
3	1279	0.5
4	719	0.9
5	460	1.5



BA 30°

H (m)	En (lx)	S (sq.m)
1	3536	0.2
2	884	0.9
3	392	1.9
4	221	3.4
5	141	5.3

