


Mondo







Down light
Integrated power supply

- White
- Black

Features



Dimensions



Tolerance: ±2mm

Electrical system

Total power consumption:	15 W
Power input:	100-240Vac, 50/60Hz
Operating temperature:	-10 °C ~ 35 °C
Power factor:	>0.95
Protection class:	Class II
Control protocol:	Non-DIM / DALI

Light source

LED type:	COB
Luminous flux:	840 lm
Colour temperature (CCT):	2700 K / 3000 K / 4000 K / Tunable
Colour consistency (SDCM):	≤2
Colour rendering index (CRI):	Ra >90
Beam angle (BA):	wallwash

Housing


Material:	Aluminium
Weight:	x,x kg

Warranty

Period:	5 years
---------	---------

Luminous intensity distribution curves

BA WW			
H (m)	En (lx)	S (sq.m)	
1	396	0,9	
2	99	3,4	
3	44	7,7	
4	25	13,7	
5	16	21,4	



Nomenclature

Type	Series name	System power	CCT	CRI	Beam angle	Control	Colour
DL02	Claro	15 (15W)	27 (2700K)	90 (90)	WW (Wallwash)	N (Non-Dim)	01 (Black)
DL03			30 (3000K)			D (DALI-DT6)	02 (White)
			40 (4000K)				
			TW (2700-5700K)			E (DALI-DT8)	

*Applicable model: DL0x15xx90WWxxx (xx: dynamic codes)